


# UPRIGHT CHILLER


- Blower System
- Magnetic Solid Door



BS 2DUC/C  
2 Door




Top View




Front View



BS 4DUC/C  
4 Door




Top View




Front View



BS 6DUC/C  
6 Door



Top View



Front View

## HIGHLIGHTS

**High-density Cyclo-isopentane Polyurethane**  
insulated body saves energy.

**Automatic defrost system**  
saves energy consumption and provide shortest possible defrost cycle.

**Refrigeration system protected from corrosion**  
by urethane-treated evaporator coil.

**Blower system (assisted with fan)**  
will ensure homogenous coolness in the storage space.

**Magnetic and robust stainless steel door.**  
Offer a higher tensile strength, which means fewer dents and scratches.

**Environmentally friendly refrigerant**  
(CFC and HCFC Free) R134a.

**Effective counter – balanced weight system self**  
closing door provides smooth, even, positive closure.

**127 ~ 152mm adjustable stainless steel legs**  
or 100mm castor wheel.

**4 tier removable and adjustable shelves.**

**Self contained system**  
no plumbing required.

**Tested at ambient temperature of 38°C,**  
with no load.

## TABLE INFO



	2 DOOR	4 DOOR	6 DOOR
<b>MODEL</b>	<b>BS 2DUC/C</b>	<b>BS 4DUC/C</b>	<b>BS 6DUC/C</b>
Temperature°C (celsius)	+2 to +8	+2 to +8	+2 to +8
External Dimension (mm)	660 x 760 x 2060	1300 x 760 x 2060	1940 x 760 x 2060
Internal Dimension (mm)	540 x 640 x 1460	1180 x 640 x 1460	1820 x 640 x 1460
Gross Volume (Litres)	505	1103	1701
Voltage/ Frequency (V/ Hz)	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz
Weight (kgs)	97	168	201
Compressor	1/4Hp	2/5Hp	1/2Hp
Wattage (W)	475 - 525	760 - 840	801 - 885
Ampere (A)	3.3 - 3.7	4.7 - 5.3	5.4 - 6.0
Energy Consumption (kw/ 24h)	4.1 - 4.5	5.9 - 6.5	11.2 - 12.4
Refrigerant/ Grams	R134a / 380g	R134a / 460g	R134a / 500g
Defrost System	Forced Air Circulation	Forced Air Circulation	Forced Air Circulation
Temperature Control	Digital	Digital	Digital
Shelves (Pvc)	4	8	12
Number Of Clips	16	32	48
Unit For 20ft Container	23	11	7
Unit For 40ft Container	48	23	15

\*Note:-  
Option : CW - Castor Wheel / BF - Bullet Feet

As product improvement is an on going process, we reserve the right to change specifications or design without notice.