



Diaphragm Gas Meter GTG_G2.5



GTG-G4

The Spec of GTG_G4

Sort	Spec.
Maximum utility flux (m ³ /h)	6.0
Minimum utility flux (m ³ /h)	0.040
Maximum utility pressure (KPa)	10 (mmH ₂ O), 50 (5000mmH ₂ O)
DEV (dm ³ /Rev)	1.3
Maximum indication (m ³)	99999.999
Minimum indication (dm ³)	0.2
Measurement accuracy (%)	Qmin≤Q<0.1Qmax:±3.0%, 0.1Qmax≤Q≤Qmax:±1.5%
Input · Output direction	Left, Right
Input · Output distance (mm)	130
Input · Output screw thread	M34X1.5
Utility temperature	-20℃ ~ +60℃
Weight (kg)	1.95
Utility gas	LNG, LPG
Accessory	Union nut (M34XP1.5), Closed gasket, The support, Bolt



Diaphragm Gas Meter GTG6-0/6-1/6-2



GTG6-0



GTG6-1



GTG6-2

The Spec of GTG_G6-0 / G6-1 / G6-2

Sort	The Spec of GTG_G6-0	The Spec of GTG_G6-1	The Spec of GTG_G6-2
Maximum utility flux (m ³ /h)		10.0	
Minimum utility flux (m ³ /h)		0.060	
Maximum utility pressure (KPa)		50 (5000mmH ₂ O)	
DEV (dm ³ /Rev)		2.4	
Maximum indication (m ³)		99999.999	
Minimum indication (dm ³)		0.2	
Measurement accuracy (%)		Qmin≤Q<0.1Qmax:±3.0%, 0.1Qmax≤Q≤Qmax:±1.5%	
Input · Output direction		Left, Right	
Input · Output distance (mm)	130	130	250
Input · Output screw thread	M34X1.5P (130mm)	PF 1 1/4" 130mm	PF 1 1/4" 250mm
Utility temperature		-20℃ ~ +60℃	
Weight (kg)	2.80	2.80	3.00
Utility gas		LNG, LPG	
Accessory	Union (PT 3/4inch)	Union (PT 1inch)	Union (PT 1inch)
	Union nut, Closed gasket, The support, Bolt		