


# REFRIGERATED BARLINE - WITHOUT BACK SPLASH

- Blower System
- Without Backsplash
- Heated Glass




B 2D/C5/7-S  
B 2D/C6/7-S

2 Door




Top View




Front View

B 3D/C7/7-S

3 Door




Top View




Front View

B 4D/C8/7-S

4 Door



Top View



Front View

## HIGHLIGHTS

Specifically design for  
beverage storage and display.

Brilliant illumination of products  
creates impulse sales.

High-density Cyclo-isopentane Polyurethane  
insulated body saves energy.

Automatic defrost system  
saves energy consumption and provide shortest possible defrost cycle.

Refrigeration system protected from corrosion  
by urethane-treated evaporator coil.

Blower system (assisted with fan)  
will ensure homogenous coolness in the storage space.

Magnetic and Heated Glass Door.

Environmentally friendly refrigerant  
(CFC and HCFC Free) R134a.

Effective counter – balanced weight system self  
closing door provides smooth, even, positive closure.

127 ~ 152mm adjustable stainless steel legs  
or 100mm castor wheel.

2 tier removable and adjustable shelves.

Tested at ambient temperature of 32°C,  
with no load.

## TABLE INFO



	2 DOOR	2 DOOR	3 DOOR	4 DOOR
MODEL	B 2D/C5/7-S	B 2D/C6/7-S	B 3D/C7/7-S	B 4D/C8/7-S
Temperature°C (celsius)	+2 to +8	+2 to +8	+2 to +8	+2 to +8
External Dimension (mm)	1500 x (760+50) x 840	1800 x (760+50) x 840	2100 x (760+50) x 840	2400 x (760+50) x 840
Internal Dimension (mm)	987 x 584 x 584	1282 x 584 x 584	1597 x 584 x 584	1900 x 584 x 584
Gross Volume (Litres)	337	437	545	648
Voltage/ Frequency (V/ Hz)	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz
Weight (kgs)	107	117	143	158
Compressor	1/4Hp	1/4Hp	1/3Hp	2/5Hp
Wattage (W)	570 - 630	570 - 630	665 - 735	713 - 787
Ampere (A)	3.8 - 4.2	3.8 - 4.2	4.3 - 4.7	4.6 - 5.0
Energy Consumption (kw/ 24h)	3.8 - 4.2	5.1 - 5.7	7.4 - 8.2	10.4 - 11.4
Refrigerant/ Grams	R134a / 340g	R134a / 360g	R134a / 360g	R134a / 370g
Defrost System	Forced Air Circulation	Forced Air Circulation	Forced Air Circulation	Forced Air Circulation
Temperature Control	Digital	Digital	Digital	Digital
Shelves (PVC)	4	4	6	8
Number Of Clips	16	16	24	32
Unit For 20ft Container	20	14	14	8
Unit For 40ft Container	42	28	28	16

\*Note:-

Option : CW - Castor Wheel / BF - Bullet Feet

As product improvement is an on going process, we reserve the right  
to change specifications or design without notice.